

# PRODUCT DATASHEET

## Tracklight Pendant Cylinder GU10 Black

Tracklight Pendant | Tracklight pendant with socket GU10



---

### Areas of application

- Kitchens, living rooms, children's rooms or home offices

---

### Product benefits

- Elegant design
- Quick and easy lamp replacement
- Adjustable in height

---

### Product features

- Suitable for lamps with GU10 base
- Housing material: metal



TECHNICAL DATA

Electrical data

|                  |             |
|------------------|-------------|
| Nominal voltage  | 220...240 V |
| Mains frequency  | 50...60 Hz  |
| Protection class | I           |

Photometrical data

|                            |   |
|----------------------------|---|
| Flickering metric (Pst LM) | - |
|----------------------------|---|

Dimensions & Weight

|                |            |
|----------------|------------|
| Diameter       | 55.00 mm   |
| Height         | 1500.00 mm |
| Product weight | 400.00 g   |

TRACKLIGHT PENDANT  
CYLINDER BK GU10

Materials & Colors

|                 |        |
|-----------------|--------|
| Product color   | Black  |
| Housing color   | Black  |
| Body material   | Steel  |
| Mercury content | 0.0 mg |

Application & Mounting

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Type of protection        | IP20         |
| Dimmable                  | No           |
| Mounting type             | Suspended    |
| Application environment   | Indoor       |
| With light source         | No           |
| Replaceable light source  | No           |
| Holder designation        | GU10         |

Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

#### Additional product data

|                       |   |
|-----------------------|---|
| Number of illuminants | 1 |
|-----------------------|---|

#### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name               |
|------------------------------------------------------------------------------------|----------------------------------------|-----------------------------|
|  | User instruction / safety instructions | TRACKLIGHT PENDANT CYLINDER |
|  | Declarations of conformity             | TRACKLIGHT PENDANT CYLINDER |
|  | Declarations of conformity UKCA        | Fixed LUM without EMC       |

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854012754 | Folding box<br>1             | 70 mm x 76 mm x 264 mm               | 458.00 g     | 1.40 dm <sup>3</sup>  |
| 4099854116131 | Shipping box<br>4            | 166 mm x 152 mm x 280 mm             | 1974.00 g    | 7.06 dm <sup>3</sup>  |
| 4099854012761 | Shipping box<br>12           | 300 mm x 246 mm x 284 mm             | 5938.00 g    | 20.96 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.