

PRODUCT DATASHEET

SMART WIFI A60 9W 230V RGBW FR E27

TRIPLE PACK

SMART+ WiFi Classic Multicolour | Classic bulb shape with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 20,000 h
- Voice control works with Hey Google or Alexa




TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220...240 V
Nominal current	60 mA
Mains frequency	50/60 Hz
Power factor λ	> 0.5
Claimed equiv. conventional lamp power	60 W
Operating mode	AC Mains

Photometrical data

Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	806 lm
Luminous flux	806 lm
Luminous efficacy	89 lm/W
Adjustable color temperature	2700...6500 K
Color temperature	2700...6500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4



Everlight 67-23ST KKE 2700K

Light technical data

Beam angle	220 °
Starting time	< 0.5 s

Warm-up time (60 %)	< 0.50 s
---------------------	----------

Dimensions & Weight



Product weight	38.00 g
Diameter	60.00 mm
Maximum diameter	60 mm
Length	112.00 mm
Width	60.00 mm
Height	60.00 mm
Outer bulb [PICOS]	A60

Lifespan

Number of switching cycles	100000
Lifespan	20000 h

Colors & materials

Product color	White
Housing color	White

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

Capabilities

Dimmable	Yes ¹⁾
----------	-------------------

Compatible smart home technology	Amazon Alexa / Google Assistant
----------------------------------	---------------------------------

1) Via App

Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	9.00 kWh/1000h
Standards	CE
Type of protection	IP20

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	⌚ 0.5 W
Networked standby power for CLS	⌚ 0.5 W
Claim of equivalent power	Yes
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	>0
Beam angle correspondence	SPHERE_360
Survival factor	0,9
Displacement factor	>0.5
LED light source replaces a fluorescent light source	No
EPREL ID	1218010
Model number	AC42222,AC42222

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	SH Insert WIFI StartUpG Lamps RGBTW LDV
	Declarations of conformity	SMART WIFI CLASSIC A
	EU Data Act	SMART WiFi Lamps and Luminaires

Photometric and lighting design files		Document name
	Spectral power distribution	Everlight 67-23ST KKE 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075778870	Folding box 3	67 mm x 130 mm x 204 mm	281.00 g	1.78 dm ³
4058075778887	Shipping box 12	270 mm x 213 mm x 145 mm	1336.00 g	8.34 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.